

Bandstahl in Stäben

nach DIN-EN 10058 bzw. DIN 1016

schwarz, warmgewalzt

S235JRG2 (RSt 37-2)

Abmessung mm	kg/m	Abmessung mm	kg/m
10 x 2	0,157	55 x 4	1,730
10 x 3	0,236	60 x 2	0,942
10 x 4	0,314	60 x 3	1,410
12 x 2	0,189	60 x 4	1,880
12 x 3	0,283	70 x 3	1,650
12 x 4	0,377	70 x 4	2,200
15 x 2	0,230	80 x 3	1,880
15 x 3	0,353	80 x 4	2,510
15 x 4	0,471	90 x 3	2,120
16 x 2	0,250	90 x 4	2,820
16 x 3	0,377	100 x 3	2,350
16 x 4	0,502	100 x 4	3,140
18 x 3	0,425	110 x 3	2,590
18 x 4	0,565	110 x 4	3,450
20 x 1	0,157	110 x 5	4,320
20 x 2	0,314	110 x 6	5,820
20 x 3	0,471	120 x 3	2,820
20 x 4	0,628	120 x 4	3,760
25 x 1	0,196	120 x 5	4,710
25 x 2	0,393	120 x 6	6,020
25 x 3	0,589	130 x 3	3,060
25 x 4	0,785	130 x 4	4,080
30 x 1	0,236	130 x 5	5,100
30 x 2	0,471	130 x 6	6,410
30 x 3	0,707	140 x 3	3,280
30 x 4	0,942	140 x 4	4,400
35 x 3	0,824	140 x 5	5,500
35 x 4	1,100	140 x 6	6,670
40 x 2	0,628	150 x 3	3,530
40 x 3	0,942	150 x 4	4,710
40 x 4	1,260	150 x 5	5,870
45 x 3	1,060	150 x 6	7,020
45 x 4	1,410		
50 x 3	1,180		
50 x 4	1,570		
55 x 3	1,300		